



راهکار های VoIP برای شرکت های بزرگ : (Large Business Solutions)

Processor Type Intel® Xeon® 5500 series
 Available processors Intel Naming Speed Cache Wattage Turbo Memory
 X5570 2.93 8M 95W 2/2/3/3 1333 MHz
 X5560 2.80 8M 95W 2/2/3/3 1333 MHz
 X5550 2.66 8M 95W 2/2/3/3 1333 MHz
 E5540 2.53 8M 80W 1/1/2/2 1066 MHz
 E5530 2.40 8M 80W 1/1/2/2 1066 MHz
 L5520 2.26 8M 60W 1/1/2/2 1066 MHz
 E5520 2.26 8M 80W 1/1/2/2 1066 MHz
 E5506 2.13 4M 80W N/A 800 MHz
 L5506 2.13 4M 60W N/A 800 MHz
 E5504 2.00 4M 80W N/A 800 MHz
 E5502 1.86 4M 80W N/A 800 MHz
 Processor Core Dual and Quad
 Processor Cache 5500 series 4M to 8 MB Level 2 Cache depending on processor
 Maximum Processor Speed 2.93 GHz
 Multi-processor 2
 Maximum Front Side Bus Speed 800-1333 MHz
 Memory Type PC3-10600R Registered (DDR3) Memory or
 PC3-10600E Unbuffered (DDR3) Memory
 Standard Memory Performance Model 12 GB (6x2 GB) DDR3-1333 MHz Registered
 Memory
 Base Model 6 GB (3x2 GB) DDR3-1333 MHz Registered Memory
 Entry Model 4 GB (2x2 GB) DDR3-1333 MHz Registered Memory
 Efficiency Model 4 GB (2x2 GB) DDR3-1333 MHz Unbuffered Memory
 Note: Memory Speed of 1333 MHz may run at (800 MHz/1066 MHz) depending on
 processor model and memory configurations. Please refer to
 Memory Configuration Tool.
 Maximum Memory 144 GB
 Memory Slots 18 DIMMs
 Advanced Memory Protection Advanced ECC
 Mirrored Memory
 Storage Type Hot plug 2.5-inch SAS
 Hot plug 2.5-inch SATA
 Hot plug 3.5-inch SAS
 Hot plug 3.5-inch SATA
 Maximum Number of Hard Drives 16 SFF
 Note: 8 SFF SAS/SATA HD Bays; optional 8 SFF drive cage (total 16); optional LFF
 SAS/SATA hard drive cage (6)
 Removable Media Bays 1
 Expansion Slot Six (6) available—optional PCI-X/PCI-Express or x16 PCI riser
 Storage Controller All models have HP Smart Array P410i embedded controller.
 Depending on the Cache configurations, the RAID support will differ:
 Entry/Efficiency Model Base Model Performance Model
 Memory/Battery Zero Memory 256 MB 512 MB BBWC
 RAID Support 0, 1, 10 0, 1, 10, 5, 50 0, 1, 10, 5, 50
 Optional Smart Array Advance Pack will allow 6, 60 RAID support and other enhanced
 features.
 Form Factor Rack
 Rack Height 2U
 Networking (2) embedded BCM5709C with dual port Gigabit Network Adapters with
 TCP/IP Offload Engine
 Infrastructure Management HP ProLiant Onboard Administrator (powered by the HP
 Integrated Lights-Out 2 management processor)
 HP Insight Control suite with new Dynamic Power Capping technology
 Redundant Power Supply Standard on performance models, optional on entry and base
 models

تا ۱۰۰۰ کاربر داخلی و ۳۲۰ خط خارجی

مشخصات نرم افزاری :

نرم افزار ARIO PBX برای ۱۰۰۰ کاربر

مشخصات سخت افزاری :

سرور:

۱- استفاده از سرور های بزرگ



GATEWAY : کارتهای PCI/PCI Express برای درگاه های دیجیتال